TABLETOP CONFERENCING DATA SHEET <

MAX[®] Wireless

Tabletop Conference Phone

The industry's first wireless tabletop conference phone. MAX Wireless provides the flexibility to hold a conference call when and where it's most convenient – with no cables in the way. MAX Wireless is a perfect fit for offices and small conference rooms, and delivers outstanding audio clarity.



UNRIVALED WIRELESS AUDIO QUALITY, FLEXIBILITY AND AFFORDABILITY

MAX WIRELESS APPLICATIONS

Small Office/Home Office

Executive Office

Small Conference Room

Any Room Without a Phone Line

MAX WIRELESS ADVANTAGES

- Superior Audio Performance
- + Distributed Echo Cancellation® effectively eliminates echo
- Noise cancellation removes background noises from fans or HVAC systems
 Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones provide 360° audio pickup
- + ClearEffect[™] provides natural, full-sounding audio without requiring wideband on both ends

Wireless Capabilities

- + Turn any room into a conference room, even one without a phone line
- + Wireless signal range allows use in multiple rooms without moving the base unit
- + Wireless design provides a clean look with no wires on the table or floor
- + 12 hours of talk time allows for lengthy conferences without recharging;
 36 hours of standby time reduces recharging frequency; automatic power-save mode conserves battery life
- + Dual-function power supply/charger enables conferencing while charging
- + Digital spread spectrum technology with 64-bit encryption ensures secure conferencing
- + Audible warnings sound when phone is out of range or needs charging
- + Phone paging button allows easy identification of phone's location

Ease of Use & Control

- + Simply plug base unit into power and phone line, charge phone, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation


ClearOne



MAX[®] Wireless Tabletop Conference Phones DATA SHEET <

> **ROOM APPLICATIONS**

MAX Wireless is a single conference phone that connects wirelessly to a base unit for use in any small room.





SPECIFICATIONS

Echo Cancellation Tail time: 60 ms x 3

Noise Cancellation Dynamic noise cancellation

Telephone Connection Analog PBX or PSTN line RJ-11C, -12 dBm nominal

Radio Frequency 2.4 GHz WDC (4) 32 kbps full duplex

Keypad Alphanumeric standard keypad

Loudspeaker Volume: 90dBspl A weighted @ 1 ft Bandwidth: 200 Hz–3.3 kHz

Record Output Connector: 2.5 mm mono audio jack Impedance: <1000 ohms Bandwidth: 200Hz–3.3kHz Dynamic range: 60dB THD <.01%

Certifications FCC part 15/ICES-003 Class A FCC part 15 Subpart C/RSS-210 FCC part 68/IC CS-03 CE

UL Certified

Power

Phone unit: Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh 12 hours continuous talk time (typical) 36 hours standby Base unit: Auto-adjusting power module; 100-240 VAC; 50/60Hz

Wireless Range Standard WDCT units: 150 ft (45 m) EU WDCT unit: 50 ft (15 m) Note: these ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

Environmental

Operating temperature: 32-118° F (0-48° C) Storage temperature: 41–158° F (5–70° C) Operating humidity: 15 to 80% Storage humidity: 10 to 90%

Dimensions (W x D x H) Phone unit:

10.5" x 10.5" x 3" (26.7 cm x 26.7 cm x 7.6 cm) Base unit: 4.25" x 5.5" x 2.5" (10.8 cm x 14 cm x 6.4 cm)

Weight Phone unit: 2.7 lb (1.2 kg) Base unit: .6 lb (0.27 kg) Shippina: MAX Wireless 10 lb (4.5 kg)

MAX Wireless Includes

Wireless phone unit (1) Base unit (1) Battery pack (1) Power supply/charger (1) Power supply retainer (1) Telephone cable Documentation CD Quick start guide

PART NUMBERS

MAX Wireless (WDCT) 910-158-400 (North America) 910-158-004 (South Korea) 910-158-006 (Hong Kong/Singapore) 910-158-007 (China) 910-158-008 (Australia/New Zealand) 910-158-009 (South Africa)

MAX Wireless (WDCT for EU) 910-158-276 (Europe/UK)

CLEARONE LOCATIONS >

Headquarters:

Salt Lake City, UT USA 5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116 Tel: 801-975-7200 800-945-7730 Fax: 801-977-0087 sales@clearone.com

Latin America

Tel: 801-974-3621 global@clearone.com

EMEA

Tel: 44 (0) 1189 036 053 global@clearone.com

APAC

Tel: 801-303-3388 global@clearone.com

© 2007 ClearOne Communications Inc. All rights reserved. Other product names may be trademarks of their respective owners. Information in this document subject to change without notice. 802-158-000 Revision 1.9 October 2007.